Gold Seal Strain Relief Connectors

Type SR

Straight Connector

Features:
- Tapered threaded male hub NPT
- Watertight/Oiltight
- UL Listed NEMA 4 & 6 when installed into a NPT threaded entry or UL Listed conduit hub (sizes 1¼" and larger require thread sealant).
- Rated at 90°C

Material/Finish:
Malleable Iron/Zinc Plated
- PVC grommets

Third Party Certification:
UL Listed: E-11857

CSA Certified: 009795

Note:
1. Gold Seal connectors available with insulated throat. Add suffix "T". Example: SR-502T. Contact your local representative for price and availability.
2. For multi-hole applications, contact your local representative for price and availability.



Type SR-502

Catalog Number	Cable Range (in.) Dia. Over Jacket Min. - Max.	Hub Size (inches)	Throat I.D.	Dimensions in Inches Body Length	Thread Length	Max. Dia.
SR-502†	.100 - .200	½	.52	1⅛	9/16	1 1/16
SR-503†	.200 - .300	½	.52	1⅛	9/16	1 1/16
SR-504†	.300 - .400	½	.52	1⅛	9/16	1 1/16
SR-505†	.400 - .500	½	.61	1 3/16	9/16	1 1/16
SR-506†	.500 - .600	½	.61	1 3/16	7/16	1 1/16
•SR-507†	.600 - .700	½	.61	1 3/16	7/16	1⅜
SR-752	.100 - .200	¾	.76	1 3/16	7/16	1⅜
SR-753	.200 - .300	¾	.76	1 3/16	7/16	1⅜
SR-754†	.300 - .400	¾	.76	1 3/16	7/16	1⅜
SR-755†	.400 - .500	¾	.76	1 3/16	7/16	1⅜
SR-756†	.500 - .600	¾	.76	1 3/16	7/16	1⅜
SR-757†	.600 - .700	¾	.76	1 3/16	7/16	1⅜
SR-758†	.700 - .800	¾	.80	1¼	7/16	1⅝
•SR-759†	.800 - .900	¾	.80	1¼	7/16	1⅝
•SR-7510†	.900 - 1.000	¾	.80	1¼	7/16	1⅝
SR-1002	.100 - .200	1	.96	1¼	⅝	1⅝
SR-1003	.200 - .300	1	.96	1¼	⅝	1⅝
SR-1004	.300 - .400	1	.96	1¼	⅝	1⅝
SR-1005	.400 - .500	1	.96	1¼	⅝	1⅝
SR-1006†	.500 - .600	1	.96	1¼	⅝	1⅝
SR-1007†	.600 - .700	1	.96	1¼	⅝	1⅝
SR-1008†	.700 - .800	1	.96	1¼	⅝	1⅝
SR-1009†	.800 - .900	1	.96	1¼	⅝	1⅝
•SR-10010†	.900 - 1.000	1	.96	1¼	⅝	1⅝
•SR-10012†	1.000 - 1.200	1	.96	1⅜	⅝	1 15/16
SR-12510†	.900 - 1.000	1¼	1.20	1⅜	⅝	2 1/16
SR-12512†	1.000 - 1.200	1¼	1.20	1⅜	⅝	2 1/16
•SR-12514†	1.200 - 1.400	1¼	1.22	1 9/16	⅝	2⅜
SR-15012†	1.000 - 1.200	1½	1.50	1 9/16	⅝	2⅜
SR-15014†	1.200 - 1.400	1½	1.50	1 9/16	⅝	2⅜
•SR-15016†	1.400 - 1.600	1½	1.56	1 13/16	⅝	3
•SR-15018†	1.600 - 1.800	1½	1.56	1 13/16	⅝	3
SR-20014†	1.200 - 1.400	2	1.93	2 1/16	⅝	3
SR-20016†	1.400 - 1.600	2	1.93	2 1/16	⅝	3
SR-20018†	1.600 - 1.800	2	1.93	2 1/16	⅝	3
SR-25018†	1.500 - 1.800	2½	2.44	2½	1⅛	4 1/16
SR-25021†	1.800 - 2.100	2½	2.44	2½	1⅛	4 1/16
SR-25024†	2.100 - 2.400	2½	2.44	2½	1⅛	4 1/16
SR-30018†	1.500 - 1.800	3	2.44	2½	1⅛	4 1/16
SR-30021†	1.800 - 2.100	3	2.44	2½	1⅛	4 1/16
SR-30024†	2.100 - 2.400	3	2.44	2½	1⅛	4 1/16

•Remove enough jacket to get conductors through Throat I.D.
†UL Listed NEMA 4, 6 & 12 when installed into a NPT threaded entry or UL Listed conduit hub.

Copyright 2007

Gold Seal Strain Relief Connectors

Type SR

Straight Connector

Features:
- Tapered threaded male hub NPT
- Watertight/Oiltight
- UL Listed NEMA 4 & 6 when installed into a NPT threaded entry or UL Listed conduit hub (sizes 1¼" and larger require thread sealant).
- Rated at 90°C

Material/Finish:
Malleable Iron/Zinc Plated
- PVC grommets

Third Party Certification:
UL Listed: E-11857

CSA Certified: 009795

Note:
1. Gold Seal connectors available with insulated throat. Add suffix "T". Example: SR-502T. Contact your local representative for price and availability.
2. For multi-hole applications, contact your local representative for price and availability.



Type SR-502

Catalog Number	Cable Range (in.) Dia. Over Jacket Min. - Max.	Hub Size (inches)	Throat I.D.	Dimensions in Inches Body Length	Thread Length	Max. Dia.
SR-502†	.100 - .200	½	.52	1⅛	9/16	1 1/16
SR-503†	.200 - .300	½	.52	1⅛	9/16	1 1/16
SR-504†	.300 - .400	½	.52	1⅛	9/16	1 1/16
SR-505†	.400 - .500	½	.61	1 3/16	9/16	1 1/16
SR-506†	.500 - .600	½	.61	1 3/16	7/16	1 1/16
•SR-507†	.600 - .700	½	.61	1 3/16	7/16	1⅜
SR-752	.100 - .200	¾	.76	1 3/16	7/16	1⅜
SR-753	.200 - .300	¾	.76	1 3/16	7/16	1⅜
SR-754†	.300 - .400	¾	.76	1 3/16	7/16	1⅜
SR-755†	.400 - .500	¾	.76	1 3/16	7/16	1⅜
SR-756†	.500 - .600	¾	.76	1 3/16	7/16	1⅜
SR-757†	.600 - .700	¾	.76	1 3/16	7/16	1⅜
SR-758†	.700 - .800	¾	.80	1¼	7/16	1⅝
•SR-759†	.800 - .900	¾	.80	1¼	7/16	1⅝
•SR-7510†	.900 - 1.000	¾	.80	1¼	7/16	1⅝
SR-1002	.100 - .200	1	.96	1¼	⅝	1⅝
SR-1003	.200 - .300	1	.96	1¼	⅝	1⅝
SR-1004	.300 - .400	1	.96	1¼	⅝	1⅝
SR-1005	.400 - .500	1	.96	1¼	⅝	1⅝
SR-1006†	.500 - .600	1	.96	1¼	⅝	1⅝
SR-1007†	.600 - .700	1	.96	1¼	⅝	1⅝
SR-1008†	.700 - .800	1	.96	1¼	⅝	1⅝
SR-1009†	.800 - .900	1	.96	1¼	⅝	1⅝
•SR-10010†	.900 - 1.000	1	.96	1¼	⅝	1⅝
•SR-10012†	1.000 - 1.200	1	.96	1⅜	⅝	1 15/16
SR-12510†	.900 - 1.000	1¼	1.20	1⅜	⅝	2 1/16
SR-12512†	1.000 - 1.200	1¼	1.20	1⅜	⅝	2 1/16
•SR-12514†	1.200 - 1.400	1¼	1.22	1 9/16	⅝	2⅜
SR-15012†	1.000 - 1.200	1½	1.50	1 9/16	⅝	2⅜
SR-15014†	1.200 - 1.400	1½	1.50	1 9/16	⅝	2⅜
•SR-15016†	1.400 - 1.600	1½	1.56	1 13/16	⅝	3
•SR-15018†	1.600 - 1.800	1½	1.56	1 13/16	⅝	3
SR-20014†	1.200 - 1.400	2	1.93	2 1/16	⅝	3
SR-20016†	1.400 - 1.600	2	1.93	2 1/16	⅝	3
SR-20018†	1.600 - 1.800	2	1.93	2 1/16	⅝	3
SR-25018†	1.500 - 1.800	2½	2.44	2½	1⅛	4 1/16
SR-25021†	1.800 - 2.100	2½	2.44	2½	1⅛	4 1/16
SR-25024†	2.100 - 2.400	2½	2.44	2½	1⅛	4 1/16
SR-30018†	1.500 - 1.800	3	2.44	2½	1⅛	4 1/16
SR-30021†	1.800 - 2.100	3	2.44	2½	1⅛	4 1/16
SR-30024†	2.100 - 2.400	3	2.44	2½	1⅛	4 1/16

•Remove enough jacket to get conductors through Throat I.D.
†UL Listed NEMA 4, 6 & 12 when installed into a NPT threaded entry or UL Listed conduit hub.

Copyright 2007