

Surge Protection Devices

2



Product Description

Due to the evolution of electronics and microprocessors in the home, there is a continuous challenge to provide quality (clean) power for electronic loads such as appliances, computers/home office and entertainment systems. Surges caused by lightning, utility grid switching and other sources travel on current carrying conductors throughout the home, which can effect and destroy sensitive electronic loads.

Eaton offers a comprehensive family of surge products for use at service entrance and point-of-use locations. These products can help protect sensitive electronics against the damaging effects of surges.

Application Description

Two-Stage Protection

Two stages of surge suppression are recommended to provide the best protection for electronic equipment. Two-stage surge suppression should be provided for all cables entering a home, including power, Internet, coaxial and telephone.

Service Entrance Surge Protection

Eaton's service entrance surge protection units provide premier surge protection for AC power at the service entrance. These products provide protection for residential electrical equipment by reducing power surges to an acceptable level for surge strips to handle at the point of use.

UL 1449 3rd Edition Type 1 and Type 2 Surge Protection

- **Type 1 Surge Protective Device (SPD)**— Permanently connected Type 1 SPDs are intended for installation between the secondary of the service transformer and the line side of the service equipment overcurrent device, as well as the load side, including watt-hour meter socket enclosures and are intended to be

Contents

Description

Surge Protection Devices and Lightning Arresters

	<i>Page</i>
Standards and Certifications	99
Product Selection	100


installed without an external overcurrent protective device.

Type 1 devices are dual-rated for Type 2 applications as well, providing the highest ratings available for installation at the service entrance

- Eaton's CHSPT1 products provide Type 1 surge protection in accordance with UL 1449 3rd Edition. These units can be universally mounted outside any manufacturer's primary service equipment
- **Type 2 Surge Protective Device**—Permanently connected Type 2 SPDs are intended for installation on the load side of the service equipment overcurrent device, including SPDs located at the branch panel
 - CHSPT2 products provide Type 2 surge protection in accordance with UL 1449 3rd Edition. These units can be mounted outside of any manufacturer's loadcenter or inside an Eaton Surge/Surge Ready loadcenter. Eaton also offers accessories to the CHSPT2 line for

telephone and cable protection.

- **Factory-Installed Surge Protection**—Eaton's loadcenters with factory-installed surge protection include a CHSPT2ULTRA and a two-pole 15A circuit breaker. These loadcenters increase the effectiveness of surge protection due to reduced lead length. A modified deadfront allows for easy viewing of indicating lights for status indication



Surge Panel

- **Surge Ready Loadcenter**—The Surge-Ready loadcenter provides a mounting provision for the CHSPT2ULTRA. This loadcenter has a modified deadfront to allow for viewing of indicating lights.

Point-of-Use Surge Protection—330V Clamping Voltage, 125 Vac, 15A, 60 Hz, 1875W, UL/cUL Listed ^①

Catalog Number	EMI/RFI Noise Filter	Total Calculated Joule Rating	Max. Peak Current	Protects	Outlets	Cord Length
Ultra Series (Best) ^②						
SULT8T	Up to 40 dB	2160 joules	144 kA	AC power/phone	Eight rotating outlets (for extra plug-in space)	6-feet
SULT10TC	Up to 58 dB	2880 joules	192 kA	AC power/phone/coax cable/network	10 outlets (five fixed, five rotating for extra plug-in space)	6-feet
SULT12TC	Up to 58 dB	4320 joules	288 kA	AC power/phone/coax cable/network	12 outlets (four fixed, eight rotating for extra plug-in space)	6-feet
Max Series (Better) ^②						
SMAX7	Up to 40 dB	1080 joules	72 kA	AC power	Seven outlets with sliding covers	6-feet
SMAX7T	Up to 40 dB	1080 joules	72 kA	AC power/phone	Seven outlets with sliding covers	6-feet
SMAX7C	Up to 40 dB	1080 joules	72 kA	AC power/coax cable	Seven outlets with sliding covers	6-feet
SMAX8TC	Up to 40 dB	2160 joules	144 kA	AC power/phone/coax cable	Eight outlets with sliding covers	6-feet
Micro Series (Good) ^②						
SMICRO7	Up to 40 dB	540 joules	36 kA	AC power	Seven outlets with sliding covers	6-feet
SMICRO1	Up to 40 dB	540 joules	36 kA	AC power	One outlet	No cord/wallmount design
SMICRO1C	Up to 40 dB	540 joules	36 kA	AC power/coax cable	One outlet	No cord/wallmount design
SMICRO1T	Up to 40 dB	540 joules	36 kA	AC power/phone	One outlet	No cord/wallmount design
SMICRO6C	Up to 40 dB	540 joules	36 kA	AC power/coax cable	Six outlets	No cord/wallmount design
SMICRO6T	Up to 40 dB	540 joules	36 kA	AC power/phone	Six outlets	No cord/wallmount design
SMICRO6TC	Up to 40 dB	540 joules	36 kA	AC power/phone/coax cable	Six outlets	No cord/wallmount design
Construction Series ^②						
SCONST7	Up to 40 dB	1080 joules	72 kA	AC power	Seven outlets	6-feet



SULT8T



SULT10TC



SULT12TC



SMAX7



SMAX7T



SMAX7C



SMAX8TC



SMICRO7



SMICRO1



SMICRO1C



SMICRO1T



SMICRO6C



SMICRO6T



SMICRO6TC



SCONST7

Notes

^① Product information is based on UL 1449 2nd Edition. Product is in transition at time of print. For updated ratings/product features, refer to www.eaton.com/surgetrap.

^② For warranty details, go to www.eaton.com/surgetrap.

Surge Protection Devices

2



Product Description

Due to the evolution of electronics and microprocessors in the home, there is a continuous challenge to provide quality (clean) power for electronic loads such as appliances, computers/home office and entertainment systems. Surges caused by lightning, utility grid switching and other sources travel on current carrying conductors throughout the home, which can effect and destroy sensitive electronic loads.

Eaton offers a comprehensive family of surge products for use at service entrance and point-of-use locations. These products can help protect sensitive electronics against the damaging effects of surges.

Application Description

Two-Stage Protection

Two stages of surge suppression are recommended to provide the best protection for electronic equipment. Two-stage surge suppression should be provided for all cables entering a home, including power, Internet, coaxial and telephone.

Service Entrance Surge Protection

Eaton's service entrance surge protection units provide premier surge protection for AC power at the service entrance. These products provide protection for residential electrical equipment by reducing power surges to an acceptable level for surge strips to handle at the point of use.

UL 1449 3rd Edition Type 1 and Type 2 Surge Protection

- **Type 1 Surge Protective Device (SPD)**— Permanently connected Type 1 SPDs are intended for installation between the secondary of the service transformer and the line side of the service equipment overcurrent device, as well as the load side, including watt-hour meter socket enclosures and are intended to be

Contents

<i>Description</i>	<i>Page</i>
Surge Protection Devices and Lightning Arresters	
Standards and Certifications	99
Product Selection	100


installed without an external overcurrent protective device.

Type 1 devices are dual-rated for Type 2 applications as well, providing the highest ratings available for installation at the service entrance

- Eaton's CHSPT1 products provide Type 1 surge protection in accordance with UL 1449 3rd Edition. These units can be universally mounted outside any manufacturer's primary service equipment
- **Type 2 Surge Protective Device**—Permanently connected Type 2 SPDs are intended for installation on the load side of the service equipment overcurrent device, including SPDs located at the branch panel
 - CHSPT2 products provide Type 2 surge protection in accordance with UL 1449 3rd Edition. These units can be mounted outside of any manufacturer's loadcenter or inside an Eaton Surge/Surge Ready loadcenter. Eaton also offers accessories to the CHSPT2 line for

telephone and cable protection.

- **Factory-Installed Surge Protection**—Eaton's loadcenters with factory-installed surge protection include a CHSPT2ULTRA and a two-pole 15A circuit breaker. These loadcenters increase the effectiveness of surge protection due to reduced lead length. A modified deadfront allows for easy viewing of indicating lights for status indication



Surge Panel

- **Surge Ready Loadcenter**—The Surge-Ready loadcenter provides a mounting provision for the CHSPT2ULTRA. This loadcenter has a modified deadfront to allow for viewing of indicating lights.

Point-of-Use Surge Protection—330V Clamping Voltage, 125 Vac, 15A, 60 Hz, 1875W, UL/cUL Listed ^①

Catalog Number	EMI/RFI Noise Filter	Total Calculated Joule Rating	Max. Peak Current	Protects	Outlets	Cord Length
Ultra Series (Best) ^②						
SULT8T	Up to 40 dB	2160 joules	144 kA	AC power/phone	Eight rotating outlets (for extra plug-in space)	6-feet
SULT10TC	Up to 58 dB	2880 joules	192 kA	AC power/phone/coax cable/network	10 outlets (five fixed, five rotating for extra plug-in space)	6-feet
SULT12TC	Up to 58 dB	4320 joules	288 kA	AC power/phone/coax cable/network	12 outlets (four fixed, eight rotating for extra plug-in space)	6-feet
Max Series (Better) ^②						
SMAX7	Up to 40 dB	1080 joules	72 kA	AC power	Seven outlets with sliding covers	6-feet
SMAX7T	Up to 40 dB	1080 joules	72 kA	AC power/phone	Seven outlets with sliding covers	6-feet
SMAX7C	Up to 40 dB	1080 joules	72 kA	AC power/coax cable	Seven outlets with sliding covers	6-feet
SMAX8TC	Up to 40 dB	2160 joules	144 kA	AC power/phone/coax cable	Eight outlets with sliding covers	6-feet
Micro Series (Good) ^②						
SMICRO7	Up to 40 dB	540 joules	36 kA	AC power	Seven outlets with sliding covers	6-feet
SMICRO1	Up to 40 dB	540 joules	36 kA	AC power	One outlet	No cord/wallmount design
SMICRO1C	Up to 40 dB	540 joules	36 kA	AC power/coax cable	One outlet	No cord/wallmount design
SMICRO1T	Up to 40 dB	540 joules	36 kA	AC power/phone	One outlet	No cord/wallmount design
SMICRO6C	Up to 40 dB	540 joules	36 kA	AC power/coax cable	Six outlets	No cord/wallmount design
SMICRO6T	Up to 40 dB	540 joules	36 kA	AC power/phone	Six outlets	No cord/wallmount design
SMICRO6TC	Up to 40 dB	540 joules	36 kA	AC power/phone/coax cable	Six outlets	No cord/wallmount design
Construction Series ^②						
SCONST7	Up to 40 dB	1080 joules	72 kA	AC power	Seven outlets	6-feet



SULT8T



SULT10TC



SULT12TC



SMAX7



SMAX7T



SMAX7C



SMAX8TC



SMICRO7



SMICRO1



SMICRO1C



SMICRO1T



SMICRO6C



SMICRO6T



SMICRO6TC



SCONST7

Notes

^① Product information is based on UL 1449 2nd Edition. Product is in transition at time of print. For updated ratings/product features, refer to www.eaton.com/surgetrap.

^② For warranty details, go to www.eaton.com/surgetrap.