



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



THHN12SLBKMINICP THHN 12 Sol Black 1000' Mini CP *Southwire Company*

Catalog Number	THHN12SLBKMINICP
Manufacturer	Southwire Company
Description	600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated Both THHN and THWN. Also Rated Awm. Simpull Technology For Easier Pulling.
Weight per unit	0.0230 (lbs/ft)
Product Category	THHN-T90-STR (Stranded)

Features

Conductor Size	12
media	Yes
Number of Conductors	1
Voltage Rating	600

Material, Color, and Finish

Insulation Material	PVC
Jacket Material	Nylon

Dimensions and Weight

Length	1000
--------	------

Descriptions

Description	THHN 12 SOL BLACK 1000' MINI CP
extra long description	SWC 58026504 THHN 12 SOL CU BK CP 1
Features	SIMPull THHN copper conductors are primarily used in conduit and cable trays for services, feeders and branch circuits in commercial or industrial applications as specified in the National Electrical Code. Voltage for all applications is 600 volts. SIMpull THHN copper conductors are designed to be installed without application of a pulling lubricant.
Long Description	600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated both THHN and THWN. Also rated AWM. SIMpull Technology for easier pulling.
Product Type	THHN 12 Sol Cu BK CP 1000CP
Short Description	THHN 12 Sol Cu Bk 1000C
Special Features	No Lube

Manufacturer Information

Brand	Copper
GTIN	00032886941030
Manufacturers Part Number	58026504
UPC	032886941030



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description BUILDING WIRE

Type THHN

Availability

minimum qty 1000

Packaging

Carton 1000

Weight Per foot 0.023

Uses, Certifications, and Standards

Application Commerical