

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

THHN4YL5000 THHN 4 STR Yellow 5000'

Southwire Company

Catalog Number	THHN4YL5000
Manufacturer	Southwire Company
Description	600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon
	Sheath, Heat, Moisture, Gasoline and Oil Resistant Ii. Rated THHN
	and THWN-2. Also Rated MTW. Simpull Technology For Easier
	Pulling.
Weight per unit	0.1520 (lbs/ft)
Product Category	THHN-T90-STR (Stranded)
Features	
Conductor Size	4
media	Yes
Number of Conductors	
Voltage Rating	
Material, Color, and Finish	
Insulation Material	PVC
Jacket Material	Nylon
	Nyion
Dimensions and Weight	5000
Length	5000
Descriptions	
Description	THHN 4 STR YELLOW 5000'
extra long description	SWC 41169408 THHN 4 Str Cu SIM Yw 5
Features	Southwire [®] SIMpull THHN copper conductors are primarily used
	in conduit and cable trays for services, feeders and branch
	circuits in commercial or industrial applications as specified in the
	National Electrical Code. Voltage for all applications is 600 volts.
	SIMpull THHN copper conductors are designed to be installed
	without application of a pulling lubricant.
Long Description	600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon
	Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated THHN
	and THWN-2. Also rated MTW. SIMpull Technology for Easier
	Pulling.
Product Type	
Special Features	No Lube
Manufacturer Information	
Brand	Copper
GTIN	00032886070167
Manufacturers Part Number	41169408
UPC	032886070167



ELLIOTT **E**LECTRIC **S**UPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories

	· J
Category Description	BUILDING WIRE
Type	THHN-2
Availability	
minimum qty	5000
Packaging	
Carton	5000
Weight Per foot	0.152
Uses, Certifications, and Standards	
Application	Commerical