

ELLIOTT ELECTRIC SUPPLY 3942 Automation Way 80525-0000, CO Fort Collins Phone: 970-305-3593 Fax: 970-372-1731



TMCX0501 1/2" NPT Alu SZ1 Armored Cable Gland (.49-.90) Crouse-Hinds

Catalog Number	TMCX0501
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Terminator Ii TMCX Cable Gland, TSC Compound, Cable Range:0.49-0.90", Cable Sealing:1 (S), Metal-Cladcorrugated Armoured, Teck Armoured, Armoured Barrier and Tray Cable, Armoured Gland, Aluminum, 1/2" NPT
Weight per unit	0.6500 (lbs/each)
Product Category	BX, MC, Armored Cable Fittings
eatures	
connection	Cable OD 0.49 to 0.90 inch
dimensions	4.0500 IN X 1.7500 IN X 1.7500 IN
Material, Color, and Finish	
Color	Natural with red union nut
Finish	Untreated
Dimensions and Weight	
Size	1/2" NPT, Size 1
Descriptions	
Description	1/2" NPT ALU SZ1 ARMORED CABLE GLAND (.4990)
extra long description	CRS-H TMCX050 1 BARR GLAND 1/2 NPT
Features	TMCX II explosionproof cable glands from Eaton Crouse-Hinds Division are used to terminate armoured barrier, non-armoured barrier and TECK armoured cable in hazardous locations. Its unique design features, coupled with our fast curing Chico LiquidSeal compound, make the TMCX II the easiest and safest solution available.
Long Description	Eaton Crouse-Hinds series Terminator II TMCX cable gland, TSC compound, Cable Range: 0.49-0.90", Cable Sealing: 1 (S), Metal-cladcorrugated armoured, TECK armoured, armoured barrier and tray cable, Armoured gland, Aluminum, 1/2" NPT
Product Type	Barr Gland 1/2 NPT SZ1 Alu TSC
Special Features	2 Piece Union Design
Nanufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00662276297326
Manufacturers Part Number	TMCX050 1
UPC	662276297326



standard

Temperature Rating

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3942 Automation Way 80525-0000, CO Fort Collins Phone: 970-305-3593 Fax: 970-372-1731

Taxonomies, Classifications, and Categories	
Category Description	CORD CONNECTORS & CORD GRIPS
Туре	Cable gland
Packaging	
Carton	1
Weight Per each	0.65
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	1/2 inch NPT

-40 to + 60 Degrees C

UL and cUL Class 1, Div 1 (ABCD) Class 2 (EFG)