


ELLIOTT ELECTRIC SUPPLY 6 South Hickory 71373-0000, LA Vidalia Phone: 318-336-5113

We Deliver...Lower Cost, Quality Products, & Personal Service





TMCX0502 1/2" Cable Gland *Crouse-Hinds*

TMCX0502
Crouse-Hinds
Eaton Crouse-Hinds Series Terminator Ii TMCX Cable Gland, TSC Compound, Cable Range:0.65-1.18", Cable Sealing:2 (M),
Metal-Cladcorrugated Armoured, Teck Armoured, Armoured
Barrier and Tray Cable, Armoured Gland, Aluminum, 1/2" NPT
0.9500 (lbs/each)
BX, MC, Armored Cable Fittings

Features

connection	Cable OD 0.49 to 0.90 inch
dimensions	4.1800 IN X 2.2500 IN X 2.2500 IN

Material, Color, and Finish

Color	Natural with red union nut
Finish	Untreated

Dimensions and Weight

Size	1/2" NPT, Size 2

Descriptions

Description	1/2" CABLE GLAND
extra long description	CRS-H TMCX050 2 BARR GLAND 1/2 NPT
Features	TMCX II explosionproof cable glands from Eaton Crouse-Hinds Division are used to terminate armoured barrier, non-armoured barrier and TECK armoured cable in hazardous locations. Its unique design features, coupled with our fast curing Chico LiquidSeal compound, make the TMCX II the easiest and safest solution available.
Long Description	Eaton Crouse-Hinds series Terminator II TMCX cable gland, TSC compound, Cable Range: 0.65-1.18", Cable Sealing: 2 (M), Metal-cladcorrugated armoured, TECK armoured, armoured barrier and tray cable, Armoured gland, Aluminum, 1/2" NPT
Product Type	Barr Gland 1/2 NPT SZ2 Alu TSC
Special Features	2 Piece Union Design

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00662276298088
Manufacturers Part Number	TMCX050 2
UPC	662276298088



ELLIOTT ELECTRIC SUPPLY 6 South Hickory 71373-0000, LA Vidalia Phone: 318-336-5113 Fax: 318-336-5587

9	Fax:	31	8-	33	6-	5	5

Taxonomies, Classifications, and Ca	ategories
Category Description	CORD CONNECTORS & CORD GRIPS
Туре	Cable gland
Packaging	
Carton	1
Package	2
Weight Per each	0.95
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	1/2 inch NPT
standard	UL and cUL Class 1, Div 1 (ABCD) Class 2 (EFG)
Temperature Rating	-40 to + 60 Degrees C