



## TM CX0751L 3/4" Cable Gland *Crouse-Hinds*

Catalog Number	TM CX0751L
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Terminator II TM CX Cable Gland, Liquid Compound, Cable Range: 0.49-0.90", Cable Sealing: 1 (S), Metal-Cladcorrugated Armoured, Teck Armoured, Armoured Barrier and Tray Cable, Armoured Gland, Aluminum, 3/4" NPT
Weight per unit	0.6000 (lbs/each)
Product Category	BX, MC, Armored Cable Fittings

### Features

connection	Cable OD 0.49 to 0.90 inch
dimensions	4.0500 IN X 1.7500 IN X 1.7500 IN

### Material, Color, and Finish

Color	Natural with red union nut
Finish	Untreated

### Dimensions and Weight

Size	3/4" NPT, Size 1
------	------------------

### Descriptions

Description	3/4" CABLE GLAND
extra long description	CRS-H TM CX075 1 L BARR GLAND 3/4 NP
Features	TM CX II explosionproof cable glands from Eaton Crouse-Hinds Division are used to terminate armoured barrier, non-armoured barrier and TECK armoured cable in hazardous locations. Its unique design features, coupled with our fast curing Chico LiquidSeal compound, make the TM CX II the easiest and safest solution available.

Long Description	Eaton Crouse-Hinds series Terminator II TM CX cable gland, Liquid compound, Cable Range: 0.49-0.90", Cable Sealing: 1 (S), Metal-cladcorrugated armoured, TECK armoured, armoured barrier and tray cable, Armoured gland, Aluminum, 3/4" NPT
------------------	--

Product Type	Barr Gland 3/4 NPT SZ1 Alu Liq
Special Features	2 Piece Union Design

### Manufacturer Information

Brand	Eaton
GTIN	00662276303416
Manufacturers Part Number	TM CX075 1 L
UPC	662276303416



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2501 East 14th Avenue  
67501-0000, KS Hutchinson  
Phone: 620-860-8405  
Fax: 620-860-8406

## Taxonomies, Classifications, and Categories

Category Description	CORD CONNECTORS & CORD GRIPS
Type	Cable gland

## Packaging

Carton	1
Package	2
Weight Per each	0.6

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	3/4 inch NPT
standard	UL and cUL Class 1, Div 1 (ABCD) Class 2 (EFG)
Temperature Rating	-40 to + 60 Degrees C