

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1620 Alcock St. 79065-0000, TX Pampa Phone: 806-665-0433 Fax: 806-665-1002



TR212R 250V RK5 TD Fuse

Catalog Number	TR212R
Manufacturer	Mersen Fuses
Description	Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 2.5A Ferrule
	Tri-Onic®
Weight per unit	0.0500 (lbs/each)
Product Category	Current Limiting
Features	
AC Voltage Rating	250
amperage rating	2.5
class	Class RK5
connection	Ferrule
interrupt rating	200
Voltage Rating	250
Material, Color, and Finish	
Body Material	PolyTube
Dimensions and Weight	
Size	2 x 0.56



Descriptions

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1620 Alcock St. 79065-0000, TX Pampa Phone: 806-665-0433

Fax: 806-665-1002

Description	250V RK5 TD FUSE
extra long description	Mersen TR2-1/2R Fuse TR-R - Class R
Features	Tri-Onic TR-R current-limiting time-delay fuses are engineered for overcurrent protection of motors, transformers, service entrance equipment, feeders and branch-circuits. The time-delay characteristics of the TR-R safely handle harmless starting currents and inrush currents associated with today's motors and transformers.
Long Description	Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 2.5A Ferrule Tri-Onic®
Product Type	Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 2.5A Ferrul
Short Description	250V 2 1/2A 2x9/10 RK5 TD
Special Features	Time-delay Current-limiting AC & DC rated Optional solid state SmartSpot blown fuse indicator Time-delay for motor start-ups and transformer inrush currents without nuisance opening Current-limiting for low peak let-thru current Rejection-style design prevents replacement errors (when used with recommended fuse blocks) Easy-to-read label for quick brand recognition and replacement Metal-embossed date and catalog number for traceability and lasting identification Fiberglass body

Manufacturer Information

Type

Brand	Mersen
GTIN	00782001747664
Manufacturers Part Number	TR2-1/2R
UPC	782001747664

provides dimensional stabili

Taxonomies, Classifications, and Categories

Weight Per each

Packaging		
Carton	1	

CLASS RK5

0.05

Uses, Certifications, and Standards

Motor circuits Mains Feeders Branch circuits Transformers
Service entrance equipment General-purpose equipment
Clip
UL listed to standard 248-12 File E2137 CSA certified to standard
C22.2 no. 248.12 DC listed to UL standard 248 TRS only