



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## TRIB100 1" Pop On NM Insld Bush

*Abb Installation Products, Inc*

|                  |   |
|------------------|---|
| Catalog Number   | TRIB100   |
| Manufacturer     | Abb Installation Products, Inc  |
| Description      | 1 Inch Non Metallic Insulated Bushing, High Impact Thermoplastic For Use With Rigid/Imc Conduit |
| Weight per unit  | 0.0400 (lbs/each)   |
| Product Category | Plastic   |

### Features

|          |               |
|----------|---------------|
| Material | Thermoplastic |
|----------|---------------|

### Material, Color, and Finish

|       |      |
|-------|------|
| Color | Blue |
|-------|------|

### Dimensions and Weight

|      |        |
|------|--------|
| Size | 1-Inch |
|------|--------|

### Descriptions

|                        |   |
|------------------------|---|
| Description            | 1" POP ON NM INSLTD BUSH  |
| extra long description | ABB TRIB100 1IN BUSHING POP-ON INSU   |
| Long Description       | 1 Inch Non Metallic Insulated Bushing, High Impact Thermoplastic for Use with Rigid/IMC Conduit |
| Product Type           | 1IN Bushing Pop-On Insul  |

### Manufacturer Information

|                           |                 |
|---------------------------|-----------------|
| Brand                     | T&B Ind Fitting |
| GTIN                      | 00786210872278  |
| Manufacturers Part Number | TRIB100         |
| UPC                       | 786210872278    |

### Taxonomies, Classifications, and Categories

|                      |   |
|----------------------|---|
| Category Description | COUPLINGS, ADAPTERS, REDUCERS, BUSHINGS, & CAPS |
| Type                 | Insulated Bushing                               |

### Packaging

|                 |      |
|-----------------|------|
| Carton          | 25   |
| Weight Per each | 0.04 |

### Uses, Certifications, and Standards

|             |   |
|-------------|---|
| Application | Provides a Well Rounded Insulating Surface Over Which Conductors May Be Pulled or on Which Conductors May Bear While In Service |
| standard    | UL E13938, CSA / UL E13938, CSA   |