



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



TY253MX 11.6" 50LB BLK Nylon CBL Tie

Abb Installation Products, Inc

Catalog Number	TY253MX
Manufacturer	Abb Installation Products, Inc
Description	High Performance Cable Tie, Weather and Ultraviolet Resistant For Indoor and Outdoor Applications, Black Color Nylon 6.6, Length Of 294.64MM (11.6 Inches) For Bundle Diameter Up to 78MM (3.07 Inches), Width Of 4.83 MM (0.19 Inches), Tensile Strength Rating Of 222 Newtons (50 Pounds), Operating Temperature Of -60 Degrees Celsius (-76 F) to 105 Degrees Celsius (221 F), Bulk Pack
Weight per unit	0.0010 (lbs/each)
Product Category	Cable Ties & Wraps

Features

media	Yes
Tensile Strength	50

Dimensions and Weight

Length	11.6
Thickness	0.05
Width	0.19

Descriptions

Description	11.6" 50LB BLK NYLON CBL TIE
extra long description	ABB TY253MX CABLE TIE 50LB 11.6IN U
Long Description	High Performance Cable Tie, Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, Black Color Nylon 6.6, Length of 294.64mm (11.6 Inches) for Bundle Diameter up to 78mm (3.07 Inches), Width of 4.83 mm (0.19 Inches), Tensile Strength Rating of 222 Newtons (50 Pounds), Operating Temperature of -60 Degrees Celsius (-76 F) to 105 Degrees Celsius (221 F), Bulk Pack
Product Type	Cable Tie 50LB 11.6IN Uv Black Nylo
Special Features	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

Brand	Ty-Rap
GTIN	00786210715049
Manufacturers Part Number	TY253MX
UPC	786210715049

Taxonomies, Classifications, and Categories

Type	HIGH PERFORMANCE
------	------------------

Availability

minimum qty	1000
-------------	------

Packaging

Carton	1000
Weight Per each	0.001

Uses, Certifications, and Standards

standard	UL E49405
----------	-----------