

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

149 North Wilson St. 76028-0000, TX Burleson Phone: 817-447-0192

Fax: 817-426-1193



U065F1 60A GD Acd F 10HP Steel N3R

Catalog Number	U065F1
Manufacturer	Industrial Conn & Sol
Description	Safety Switch, 60 A, 240 V, 1 Phase, 10 HP, Fusible Fuse, Thermoplastic, #14 to #8 Awg (Solid);#14 to #3 Awg (Stranded Copper);#12 to #8 Awg (Solid);#12 to #3 Awg (Stranded Aluminum);#12 to #8 Awg (Solid);#12 to #2 Awg (Stranded Aluminum/Copper) Wire Size, 5 In Overall Length, 2-3/4 In Overall Width, 9 In Overall Height, Fusible
Weight per unit	3.5 (lbs/each)
Product Category	Fusible Disconnect Safety Swit
eatures	
amperage rating	60
interrupt rating	10000
Voltage Rating	240
Dimensions and Weight	
Size	5 X 9
Descriptions	
Description	60A GD ACD F 10HP STEEL N3R
extra long description	MIDWEST U065F1 MW 60A GD ACD F 10H
Special Features	Pullers are removable or reinstallable in the OFF position for use safety during equipment maintenance Door has padlock provisions to prevent unauthorized access Noryl thermoplastic enclosure is corrosion resistant and extremely durable, giving long maintenance free service Three-piece construction that opens up mounting and wiring areas, reduces installation time Numerous knockouts reduce installation time Straight-in, straight-out wiring saves time and money FR65 complete block and block, F682 puller
Nanufacturer Information	
Brand	MIDWEST
GTIN	00784567300055

Brand	MIDWEST
GTIN	00784567300055
UPC	784567300055

Taxonomies, Classifications, and Categories

Category Description	TEMP. POWER PANELS & ACCESSORIES
Туре	Fused Pull-Out AC Disconnect Switch



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

149 North Wilson St. 76028-0000, TX Burleson Phone: 817-447-0192 Fax: 817-426-1193

Packaging	
Carton	1
Package	6
Weight Per each	3.5
Uses, Certifications, and Standards	
Enclosure	Metallic
Mounting	SURFACE

UL/cUL Listed