

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

4000 Mockingbird Ln 79109-3210, TX Amarillo Phone: 806-220-0404 Fax: 806-220-0811



Туре

UNY50NR 1/2" Male Union Appleton/Oz Gedney

Catalog Number	UNY50NR
Manufacturer	Appleton/Oz Gedney
Description	Unilets Uny Union, Trade Size: 1/2 In, Outside Diameter: 1.47 In, Length: 2.147 In, Flexibility: Rigid and Imc, Material: Steel, Connection: Male Threaded X Female Threaded, Finish: Zinc Electroplate, Standard: UI 886 (1203), UI File Numb
Weight per unit	0.3400 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel
Features	
connection	Male Threaded X Female Threaded
outside diameter	1.47
Dimensions and Weight	
Length	2.147
Descriptions	
Description	1/2" MALE UNION
extra long description	APP UNY50NR 1/2 UNION CONNECTOR TYP
Long Description	UNILETS UNY Union, Trade Size: 1/2 IN, Outside Diameter: 1.47 IN, Length: 2.147 IN, Flexibility: Rigid And IMC, Material: Steel, Connection: Male Threaded X Female Threaded, Finish: Zinc Electroplate, Standard: UL 886 (1203), UL File Numb
Product Type	1/2 Union Connector Type
Special Features	Accurately tapped, tapered threads for tight, rigid joints and ground continuity;Concentric ring interlocked design sizes makes possible smaller diameter, allowing use in tighter spaces;Explosionproof, dust-ignitionproof;Nipple not removable;Smooth, rounded integral bushing in each hub protects conductor insulation;UNY unions are used for joining conduit and connecting conduit to enclosures, Facilitates modifications, permits removal of enclosures without turning or removal of conduit
Manufacturer Information	
Brand	Appleton
GTIN Manufacturers Part Number	00781381234221 UNY50NR
	781381234221
Taxonomies, Classifications, and C Category Description	Categories HAZARDOUS LOCATION FITTINGS
-	

UNY Union



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

4000 Mockingbird Ln 79109-3210, TX Amarillo Phone: 806-220-0404 Fax: 806-220-0811

Trade Size	1/2
Packaging Carton	10
Package	50
Weight Per each	0.34
Uses, Certifications, and Standards Application	For Connecting Conduit To Enclosure
standard	and Class III, CSA C22.2 No. 25, C22.2 No. 30, CSA 065181 Certified;Class II, Groups E, F, G;UL 886 (1203), UL File Number E10444, UL Listed for Class I, Groups A, B, C, d