# **Specifications**

#### Photo is representative



## Eaton UTTE7213TCH

Eaton meter socket, commercial or resi se 200A, Over/under, 5 hub open, #6-350 kc jaw, three-ph, #6-350 Lever bypass, Two grounding conns (#1 Cu), Quadplex, 4-wi Ringless, 600 Vac

General specification

PRODUCT NAME

CATALOG

NUMBER UPC

PRODUCT

PRODUCT

HEIGHT PRODUCT

WIDTH PRODUCT

WEIGHT

WARRANTY

CERTIFICATIONS

LENGTH/DEPTH

Product, whichever occurs first.

UL Listed

### Product specifications

CH et, 1-pos si service, r, 5x5 inch kcmil, 7- -350 kcmil, 70 (#14-#2 -wire,	ТҮРЕ	Single- position commercial or residential service
	AMPERAGE RATING	200A
	FEED TYPE	Top/bottom
	NUMBER OF JAWS	Seven-jaw
	PHASE	Three- phase
c	UTILITY APPROVALS	IL : Ameren MO : Ameren
ations Eaton meter socket	LINE	#6-350 kcmil
	LOAD	#6-350 kcmil
UTTE7213TCH 786685351346	NUMBER OF WIRES	Four-wire
4.94 in	HUB TYPE	5 x 5 hub opening
10.	SECURITY	Ringless
19 in	VOLTAGE RATING	600 V
13 in	BYPASS	Lever
25 lb	NUMBER OF SOCKETS	1
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Declarat		



# **Specifications**

#### Photo is representative



## Eaton UTTE7213TCH

Eaton meter socket, commercial or resi se 200A, Over/under, 5 hub open, #6-350 kc jaw, three-ph, #6-350 Lever bypass, Two grounding conns (#1 Cu), Quadplex, 4-wi Ringless, 600 Vac

General specification

PRODUCT NAME

CATALOG

NUMBER UPC

PRODUCT

PRODUCT

HEIGHT PRODUCT

WIDTH PRODUCT

WEIGHT

WARRANTY

CERTIFICATIONS

LENGTH/DEPTH

Product, whichever occurs first.

UL Listed

### Product specifications

CH et, 1-pos si service, r, 5x5 inch kcmil, 7- -350 kcmil, 70 (#14-#2 -wire,	ТҮРЕ	Single- position commercial or residential service
	AMPERAGE RATING	200A
	FEED TYPE	Top/bottom
	NUMBER OF JAWS	Seven-jaw
	PHASE	Three- phase
c	UTILITY APPROVALS	IL : Ameren MO : Ameren
ations Eaton meter socket	LINE	#6-350 kcmil
	LOAD	#6-350 kcmil
UTTE7213TCH 786685351346	NUMBER OF WIRES	Four-wire
4.94 in	HUB TYPE	5 x 5 hub opening
10.	SECURITY	Ringless
19 in	VOLTAGE RATING	600 V
13 in	BYPASS	Lever
25 lb	NUMBER OF SOCKETS	1
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Declarat		

