



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



UU605025 23.9X19.5X10.6 N4X FG SLD HC

Hoffman Enclosures, Inc.

| | |
|------------------|--|
| Catalog Number | UU605025 |
| Manufacturer | Hoffman Enclosures, Inc. |
| Description | Ultrx Enclosure Solid Door Type 4X, 600X500X250MM, LT Gray, Fiberglass |
| Weight per unit | 32.5 (lbs/each) |
| Product Category | Nema Types 4, 4X, 12 & 13 |

Features

| | |
|-----------|------------|
| ip rating | IP66 |
| Material | Fiberglass |

Material, Color, and Finish

| | |
|------------|--------------|
| Color | Light Gray |
| Color Code | RAL 7035 |
| Finish | Smooth Matte |

Dimensions and Weight

| | |
|--------|------------------|
| Depth | 10.94 |
| Height | 24.61 |
| Size | 24.61 x 20.20 in |
| Width | 20.2 |

Descriptions

| | |
|------------------------|---|
| Description | 23.9X19.5X10.6 N4X FG SLD HC |
| extra long description | NVENT HOF UU605025 Enclosure 600x50 |
| Features | Providing outstanding protection against corrosion and the elements, the clean lines and molded, embossed design of Ultrx fiberglass enclosures make them the most stylish and aesthetically pleasing of their class. |
| Long Description | Ultrx Enclosure Solid Door Type 4X, 600x500x250mm, Lt Gray, Fiberglass |
| Product Type | Enclosure 600X500X250MM |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Nvent Hoffman |
| GTIN | 00783510358204 |
| Manufacturers Part Number | UU605025 |
| UPC | 783510358204 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|---|
| Category Description | VYNCKIER FIBERGLASS ENCLOSURES |
| Type | Fiberglass and Thermoplastic Wall Mounted Industrial Enclosures |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Weight Per each | 32.5 |

Uses, Certifications, and Standards

| | |
|-------------|---|
| Application | Corrosive Environments; Controls and Drives |
| nema rating | 4X Watertight, corrosion-resistant |