Specifications



Photo is representative

Eaton V48M28T1216

Eaton General purpose ventilated transformer, Fungus proof, AL windings, DOE 2016, NEMA 2, FR943, 220°C, 112.5 kVA, Fl/wall mt uprt, 3-phase, PV: 480V delta, SV: 208Y/120, NEMA ST-20, 2 at +2.5%, 4 at -2.5%, 150°C, 112.5 kVA, WS60, 280B

General specifications	
PRODUCT NAME	Eaton General purpose ventilated transformer
CATALOG NUMBER	V48M28T1216
UPC	786680147234
PRODUCT LENGTH/DEPTH	31.5 in
PRODUCT HEIGHT	51 in
PRODUCT WIDTH	34.5 in
PRODUCT WEIGHT	970 lb
WARRANTY	Eaton Selling Policy 25- 000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	DOE2016 Efficient
CERTIFICATIONS	UL Listed
CATALOG NOTES	10 CFR Part 431 (2016) Efficient



Physical Attributes	
COIL MATERIAL	Aluminum
ENCLOSURE	NEMA 2
FRAME	FR943
INSULATION	220 °C
MOUNTING	Floor or wall, upright only
TAP SIZE	2 at +2.5%, 4 at -2.5%
ТҮРЕ	Energy-efficient ventilated dry-type transformer
WIRING CONNECTION	280B

Performance Ratings		
EFFICIENCY	10 CFR Part 431-2016 (DOE 2016)	
FREQUENCY RATING	60 Hz	
KVA RATING	112.50 kVA	
PRIMARY VOLTAGE	480 V delta	
SECONDARY VOLTAGE	208Y/120 V	
SOUND LEVEL	NEMA ST-20	
TEMPERATURE RISE	150 °C rise	
VOLT AMPERE RATING	112.5 kVA	
VOLTAGE RATING	480 Vac-208Y/120 Vac	

Miscellaneous		
WEATHERSHIELD	WS60	

Resources	
BROCHURES	Eaton's low-voltage dry- type distribution transformers
	Eaton's high-efficiency dry- type transformers
SPECIFICATIONS AND DATASHEETS	<u>Eaton Specification Sheet - V48M28T1216</u>

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

latest product and support information.







Follow us on social media to get the



