


ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





V5711RH Internal Twisted Elbow RH Wiremold/Legrand

Catalog Number	V5711RH
Manufacturer	Wiremold/Legrand
Description	<p>For 90 Degree Twist With A 90 Degree Turn. For Double Turn</p>
	At Right Angles From One Surface to Another. For Transitions
	From A Sidewall to Ceiling or Edge Of Door or Window Trim.
	Twistout In Cover Adapts For Use With 700 Series Raceway.
Weight per unit	0.1760 (lbs/each)
Product Category	Metallic Raceway & Accessories

Features

indoor/outdoor	Indoor	
Material	Steel	
Voltage	600.0 V	

Material, Color, and Finish

Color	lvorv

Descriptions

Description	INTERNAL TWISTED ELBOW RH
extra long description	WM V5711RHA INTERNAL 90 DEG TWISTED
Features	For 90 degree twist with a 90 degree turn. For double turn at right angles from one surface to another. For transitions from a sidewall to ceiling or edge of door or window trim. Twistout in cover adapts for use with 700 Series Raceway.
Long Description	For 90 degree twist with a 90 degree turn. For double turn at right angles from one surface to another. For transitions from a sidewall to ceiling or edge of door or window trim. Twistout in cover adapts for use with 700 Series Raceway.
Product Type	Internal 90 Deg Twisted Right Hand
Special Features	Low-profile, unobtrusive appearance. Blends with any décor or setting. ScuffCoat finish, tough, durable, scratch-resistant can be overpainted with latex paint. Fittings have removable covers which allow easy access to wiring for changes and additions.

Manufacturer Information

Brand	WIREMOLD
GTIN	00786776042740
Manufacturers Part Number	V5711RHA
UPC	786776042740

Taxonomies, Classifications, and Categories

Category Description	Panduit & Wiremold Metallic & Non-Metallic Raceways
Туре	FITTING



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Availability Status	Inactive
Packaging Carton	10
Weight Per each	0.176
Uses, Certifications, and Standards	
standard	ROHS, USMCA, NAFTA, CULUS, cULus Listed Raceway: File E4376 Guide RJBT. Fittings: File E4751 Guide RJPR. Meets Article 386 of NEC. Meets Section 12-1600 of CEC.