

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## WF6SWW590CRIMBM6 6" 13W Led Wafer Selectable Matte Black Lithonia Lighting - Acuity

Catalog Number	WF6SWW590CRIMBM6
Manufacturer	Lithonia Lighting - Acuity
Description	The Wafer Led Downlights With Switchable White Technology Provides High-Quality Light Output and Efficiency and Features A Switch For Easy Color Temperature Adjustment, While Eliminating The Need For Recessed Housings.
Weight per unit	1.6 (lbs/each)
Product Category	Lighting
atures	
average life	50,000
dimensions	6.7 x 6.7 x 1.1
dimmable	Yes
Hardware	Yes
Lamp Included	Yes
Lamp Type	LED - Dynamic
lumens	950 lm
Material	Polycarbonate
Maximum Operating Temperature	25
Power Source	Hardwired
Shape	Round
Voltage Rating	120
Warranty	3
Wattage	
aterial, Color, and Finish	
Color	Black
color rendering index (cri)	90
color temperature	2700 ,3000 ,3500 ,4000 ,5000 ,Variable
Finish	Matte
Lens Color	WHITE
Lens Material	Polycarbonate
Style	CONTEMPORARY
mensions and Weight	
Height	1.1
Length	7
Width	6.7



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Descriptions

Construction	Canless,New Construction,Remodel
Description	6" 13W LED WAFER SELECTABLE MATTE BLACK
extra long description	LITH WF6 SWW5 90CRI MB M6 6IN wafer
Features	Contractor Select
Long Description	The Wafer LED Downlights with Switchable White technology provides high-quality light output and efficiency and features a switch for easy color temperature adjustment, while eliminating the need for recessed housings.
Product Type	Downlight
Manufacturer Information	
Brand	JUNO
GTIN	00194994243809
Manufacturers Part Number	WF6 SWW5 90CRI MB M6
UPC	194994243809
Taxonomies, Classifications, and (	
Category Description	
Туре	Downlight
Trade Size	
aperture size	6 in
Packaging	
Carton	
Package	
Weight	1.6
Weight Per each	1.6
Uses, Certifications, and Standard	ls
Application	Decorative, Hospitality, Residential, Retail
environmental conditions	Indoor,Outdoor
Mounting	Recessed
standard	CSAusCA Title 24, ENERGY STAR, FCC 47CFR Part 15 Consumer, JA8