



This high-quality Cat 6 RJ45 Keystone Connector in brown is perfect for use in all Keystone Wall Plates. The standard RCA front jack connects to Cat5, Cat5e, or Cat6 cables terminated with RJ-45 plugs. The vertical design makes punchdown termination easy, while rear retention caps ensure secure wire connections.

Features & Benefits

| | |
|--|---|
| Standard RCA front jack | Connects to Cat5, Cat5e, or Cat6 cables terminated with RJ-45 plugs Rear retention caps ensure secure wire termination |
| Vertical design for easy punchdown termination | T658A and T568B wiring labels included |
| Meets Category 6 described in TIA/EIA-568-B.2 | Insertion and extraction life is 750 Cycles Min |
| Jack housing is high-impact, flame resistant plastic, UL 94V-0 | Spring wire is phosphor bronze alloy plated with 50 micro-inch of gold over 100 micro-inches of nickel |

Specifications

General Info

| | | | |
|--------------|--------------|-------------------|---------------------------|
| Product Line | On-Q | Color | Brown |
| UPC Number | 804428024408 | Country Of Origin | Taiwan, Province Of China |

Dimensions

| | | | |
|-------------------|---------|-------------------|---------|
| Product Width US | 0.64 in | Product Height US | 0.87 in |
| Product Length US | 1.28 in | | |

Technical Information

| | | | |
|-------------------|-----------|------------|------|
| Termination Style | Punchdown | Cable Type | Cat6 |
|-------------------|-----------|------------|------|



This high-quality Cat 6 RJ45 Keystone Connector in brown is perfect for use in all Keystone Wall Plates. The standard RCA front jack connects to Cat5, Cat5e, or Cat6 cables terminated with RJ-45 plugs. The vertical design makes punchdown termination easy, while rear retention caps ensure secure wire connections.

Features & Benefits

| | |
|--|---|
| Standard RCA front jack | Connects to Cat5, Cat5e, or Cat6 cables terminated with RJ-45 plugs Rear retention caps ensure secure wire termination |
| Vertical design for easy punchdown termination | T658A and T568B wiring labels included |
| Meets Category 6 described in TIA/EIA-568-B.2 | Insertion and extraction life is 750 Cycles Min |
| Jack housing is high-impact, flame resistant plastic, UL 94V-0 | Spring wire is phosphor bronze alloy plated with 50 micro-inch of gold over 100 micro-inches of nickel |

Specifications

General Info

| | | | |
|--------------|--------------|-------------------|---------------------------|
| Product Line | On-Q | Color | Brown |
| UPC Number | 804428024408 | Country Of Origin | Taiwan, Province Of China |

Dimensions

| | | | |
|-------------------|---------|-------------------|---------|
| Product Width US | 0.64 in | Product Height US | 0.87 in |
| Product Length US | 1.28 in | | |

Technical Information

| | | | |
|-------------------|-----------|------------|------|
| Termination Style | Punchdown | Cable Type | Cat6 |
|-------------------|-----------|------------|------|