


WP4H400PSQ

Large wallpack for 400 watt floods. All aluminum precision die cast construction with tempered glass refractor. Lamp supplied.

Color: Bronze

Weight: 28.9 lbs



Lamp Info

Type: ED28
Watts: 400W
Shape/Size: N/A
Base: N/A
ANSI: N/A
Hours: 20,000
Lamp Lumens: 40,000
Efficacy: 89 LPW

Ballast Info

Type: CWA-HPF QT
120V: 3.5/4.0A
208V: 2.0/2.3A
240V: 1.8/2.0A
277V: 1.5/1.8A
Input Watts: 450W
Efficiency: 89%

Technical Specifications

UL Listing:

Suitable for wet locations. HID fixtures can be wired with 90°C supply wiring if supply wires are routed 3" away from the ballast.

Housing:

Die cast aluminum 1/2" NPS tapped holes top, both sides and back for conduit or photocontrol. Hinged refractor frame, Continuous silicone rubber gasket.

Reflector:

Specular anodized aluminum, removable for installation. Symmetrical light pattern maximizes distance between fixtures.

Refractor:

Prismatic optics designed to minimize glare and throw light down and out. Heat resistant borosilicate glass.

Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.

Pulse Start:

Pulse Start metal halide for increased lamp life, lumen maintenance, color uniformity and efficiency.

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

EISA 2007 Compliant:

This product complies with the new law for metal halide ballast efficiency. This law goes into effect January 1st, 2008. Pulse Start offers Longer Lamp Life, Faster Startup and Faster Restrike.




WP4H400PSQ

Large wallpack for 400 watt floods. All aluminum precision die cast construction with tempered glass refractor. Lamp supplied.

Color: Bronze

Weight: 28.9 lbs



Lamp Info

Type: ED28
Watts: 400W
Shape/Size: N/A
Base: N/A
ANSI: N/A
Hours: 20,000
Lamp Lumens: 40,000
Efficacy: 89 LPW

Ballast Info

Type: CWA-HPF QT
120V: 3.5/4.0A
208V: 2.0/2.3A
240V: 1.8/2.0A
277V: 1.5/1.8A
Input Watts: 450W
Efficiency: 89%

Technical Specifications

UL Listing:

Suitable for wet locations. HID fixtures can be wired with 90°C supply wiring if supply wires are routed 3" away from the ballast.

Housing:

Die cast aluminum 1/2" NPS tapped holes top, both sides and back for conduit or photocontrol. Hinged refractor frame, Continuous silicone rubber gasket.

Reflector:

Specular anodized aluminum, removable for installation. Symmetrical light pattern maximizes distance between fixtures.

Refractor:

Prismatic optics designed to minimize glare and throw light down and out. Heat resistant borosilicate glass.

Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.

Pulse Start:

Pulse Start metal halide for increased lamp life, lumen maintenance, color uniformity and efficiency.

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

EISA 2007 Compliant:

This product complies with the new law for metal halide ballast efficiency. This law goes into effect January 1st, 2008. Pulse Start offers Longer Lamp Life, Faster Startup and Faster Restrike.

