

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4000 Mockingbird Ln 79109-3210, TX Amarillo Phone: 806-220-0404 Fax: 806-220-0811



WT41500JR Wingtwist Wire Connector, WT41 Tan, 500/Jar Ideal

Catalog Number	WT41500JR
Manufacturer	Ideal
Description	Buchanan, Wire Connector, Wingtwist, Conductor Range: 22 - 10 Awg, 2/20 Awg Min, 3/10 Solid Awg Max, Number Of Conductors: 1 to 6, Material: Flame-Retardant Polypropelene, Color: Tan, Voltage Rating: 600 V, Environmental Conditions: Tough, UI 94V-2 Flame-Retardant Shell Rated At 105 Deg C (221 F), Model Number: WT41
Weight per unit	0.0040 (lbs/each)
Product Category	Electrical Fixture Conn (Nuts
Features	
Material	Flame-retardant Polypropelene
media	Yes
Voltage Rating	600
Material, Color, and Finish Color	Tan



ELLIOTT ELECTRIC SUPPLY 4000 Mockingbird Ln 79109-3210, TX Amarillo Phone: 806-220-0404

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 806-220-0811

1)	es	cr	ın	TI	n	nc
$\boldsymbol{\nu}$	C3	ы	IN	u	v	113

Description	WINGTWIST WIRE CONNECTOR, WT41 TAN, 500/JAR
extra long description	IDEAL WT41-500JR WINGTWIST WT41 TAN
Features	With a full line for virtually every wire size and combination, the WingTwist Wire Connector offers a great combination of performance and value. The contoured wing design of the WingTwist provides maximum torque for a variety of electrical applications while the copolymer shell and live-action spring expand for smooth, progressive tightening providing dependable connections. With a tough, flame-retardant shell that withstands environmental extremes, and a long, deep skirt to provide maximum dielectric prote
Long Description	Buchanan, Wire Connector, WingTwist, Conductor Range: 22 - 10 AWG, 2/20 AWG Min, 3/10 Solid AWG MAX, Number Of Conductors: 1 to 6, Material: Flame-retardant Polypropelene, Color: Tan, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: WT41
Product Type	Wingtwist WT41 Tan, 500 Jar
Special Features	1,000V Maximum In Fixtures And Signs; Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection; Features: Five Color-Coded Models Cover Common Construction Wire Ranges; Fixed, Square-Wire Spring Threads Itself Creating Secure Pressure Grip; Green Model Designed For Ground Connections; Model Number: WT41; UL 486C Listed (WGR UL 467 Listed) And CSA C22.2 #188 Certified; Unique Contoured Wing Design Acts As Built-In Wrench Providing Maximum Torque With Minimum E
nufacturer Information Brand	Ideal

Ma

Brand	ldeal	
GTIN	00781789967707	
Manufacturers Part Number	WT41-500JR	
UPC	781789967707	

Taxonomies, Classifications, and Categories

Category Description	WIRE NUTS

Availability

•	
minimum qty	500

Packaging

···~g···g		
Carton	500	
Package		
Weight Per each	0.004	

ELLIOTT ELECTRIC SUPPLY

4000 Mockingbird Ln 79109-3210, TX Amarillo Phone: 806-220-0404

Fax: 806-220-0811

Uses, Certifications, and Standards

Application	Insulating or Joining 1 or more conductors	
environmental conditions	Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (2 F)	
standard	CSA C22.2 #188, UL 486C Listed, RoHS	