



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



XHHW6BK1000 AI XHHW #6 STR Black 1000'

King Wire Inc.

Catalog Number	XHHW6BK1000
Manufacturer	King Wire Inc.
Description	1000 Volts/600 Volts Alumaflex Brand Aluminum Alloy (AA-8176) Conductor. Cross-Linked Polyethylene (Xlpe) Insulation. Moisture Resistant High Heat.
Weight per unit	0.0390 (lbs/ft)
Product Category	XHHW-STR (Stranded)

Features

Conductor Size	6 AWG
----------------	-------

Material, Color, and Finish

Conductor Material	Aluminum
Insulation Material	XLP

Descriptions

extra long description	SWC 11270601 6 STR 3E AL (13.3mm2)
Features	Southwire® SIMpull XHHW-2®/RW90 aluminum conductors are primarily used in conduit or recognized raceways for service and feeder wiring as specified in the National Electrical Code. XHHW-2 conductors may be used in wet or dry locations at temperatures not to exceed 90C. Voltage rating for XHHW-2 conductors is 1000 volts. Suitable for use in Health Care Facilities per section 517.160 of the NEC where a dielectric constant of 3.5 or less may be specified. This product is designed to be installed without the
Long Description	1000 Volts/600 Volts Alumaflex Brand Aluminum Alloy (AA-8176) Conductor. Cross-linked Polyethylene (XLPE) Insulation. Moisture Resistant High Heat.
Product Type	6 STR 3E AI (13.3MM2) Simpull(R) XHHW-2 Black 1000 FT

Manufacturer Information

Brand	Aluminum
Manufacturers Part Number	11270601

Taxonomies, Classifications, and Categories

Category Description	ALUM BUILDING WIRE
----------------------	--------------------

Availability

minimum qty	1000
-------------	------

Packaging

Carton	1000
Weight Per foot	0.039