Specifications



Photo is representative

Eaton XTCE115GS1A

Eaton XT IEC contactor, 115A, Sidemounted, 110 Vac 50 Hz, 120 Vac 60 Hz, 1NO-1NC, Frame G, 90 mm, 50-60 Hz, 10, 25, 25/40, 50, 100, 100 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, FVNR

General specifications	
PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE115GS1A
UPC	786685365152
PRODUCT LENGTH/DEPTH	1 in
PRODUCT HEIGHT	1 in
PRODUCT WIDTH	1 in
PRODUCT WEIGHT	1 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	CSA Certified UL Listed EN 60947 IEC 60947



										•	C.		7				
ı	4	m	M	П	r	п	S	n	e	ы	П	ca	Ť٦	O	Ti	ľ	۹

HP RATING - MAX	10, 25, 25/ 40, 50, 100, 100 hp (1/3PH @115,200,230/200,230,460,575 V)				
NUMBER OF POLES	Three-pole				
ТҮРЕ	Full voltage non-reversing contactor				
FREQUENCY RATING	50-60 Hz				
FRAME SIZE	90 mm				
TERMINALS	Screw terminals				
COIL	110-120 Vac, 50/60 Hz				
COIL VOLTAGE	110-120 Vac, 50/60 Hz				
CONTACT CONFIGURATION	1 NO, 1 NC				
CONTINUOUS AMPERE RATING	115 A				
SERIES	XT IEC				
OPERATION	Non-reversing				
CONTINUOUS AMPERE RATING SERIES	115 A				

SPECIFICATIONS AND	Eaton Specification Sheet -
DATASHEETS	XTCE115GS1A

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Follow us on social media to get the latest product and support information.

All other trademarks are property of their respective owners.









Specifications



Photo is representative

Eaton XTCE115GS1A

Eaton XT IEC contactor, 115A, Sidemounted, 110 Vac 50 Hz, 120 Vac 60 Hz, 1NO-1NC, Frame G, 90 mm, 50-60 Hz, 10, 25, 25/40, 50, 100, 100 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, FVNR

General specifications	
PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE115GS1A
UPC	786685365152
PRODUCT LENGTH/DEPTH	1 in
PRODUCT HEIGHT	1 in
PRODUCT WIDTH	1 in
PRODUCT WEIGHT	1 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	CSA Certified UL Listed EN 60947 IEC 60947



										•	C.		7				
ı	4	m	M	П	r	п	S	n	e	ы	П	ca	Ť٦	O	Ti	ľ	۹

HP RATING - MAX	10, 25, 25/ 40, 50, 100, 100 hp (1/3PH @115,200,230/200,230,460,575 V)				
NUMBER OF POLES	Three-pole				
ТҮРЕ	Full voltage non-reversing contactor				
FREQUENCY RATING	50-60 Hz				
FRAME SIZE	90 mm				
TERMINALS	Screw terminals				
COIL	110-120 Vac, 50/60 Hz				
COIL VOLTAGE	110-120 Vac, 50/60 Hz				
CONTACT CONFIGURATION	1 NO, 1 NC				
CONTINUOUS AMPERE RATING	115 A				
SERIES	XT IEC				
OPERATION	Non-reversing				
CONTINUOUS AMPERE RATING SERIES	115 A				

SPECIFICATIONS AND	Eaton Specification Sheet -
DATASHEETS	XTCE115GS1A

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Follow us on social media to get the latest product and support information.

All other trademarks are property of their respective owners.







