

Eaton XTCEXFAG11

Catalog Number: XTCEXFAG11

Contactor Accessory - Auxiliary Contact, Two-pole, Screw terminals, D-G Frame size, 1NO-1NC contact configuration, 16A conventional thermal rating, Front mounting, used with XTRE control relays

General specifications



Product Name

Eaton motor control auxiliary contact

Catalog Number

XTCEXFAG11

UPC

782116354702

Product Length/Depth

1.5 in

Product Height

2 in

Product Width

1 in

Product Weight

0.07 lb

Warranty

Not Applicable

Compliances

ATEX Compliant

CCC Marked

CE Marked

Certifications

IEC 60947

EN 60947

UL Listed

CSA Certified

Catalog Notes

Screw terminals (6-65A); 5 mm(80-150A); no lugs (185-2000A). Orders must be placed in multiples of package quantity listed.

Product specifications

Used with

XTRE control relays

Number Of Poles

Two-pole

Type

Contactory Accessory - Auxiliary Contact

Frame size

D-G

Terminals

Screw

Contact configuration

1 NO-1 NC

Mounting method

Front

Conventional thermal current

16A

Quantity

5

Resources

Specifications and datasheets

[Eaton Specification Sheet - XTCEXFAG11](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia

Eaton XTCEXFAG11

Catalog Number: XTCEXFAG11

Contactor Accessory - Auxiliary Contact, Two-pole, Screw terminals, D-G Frame size, 1NO-1NC contact configuration, 16A conventional thermal rating, Front mounting, used with XTRE control relays

General specifications



Product Name

Eaton motor control auxiliary contact

Catalog Number

XTCEXFAG11

UPC

782116354702

Product Length/Depth

1.5 in

Product Height

2 in

Product Width

1 in

Product Weight

0.07 lb

Warranty

Not Applicable

Compliances

ATEX Compliant

CCC Marked

CE Marked

Certifications

IEC 60947

EN 60947

UL Listed

CSA Certified

Catalog Notes

Screw terminals (6-65A); 5 mm(80-150A); no lugs (185-2000A). Orders must be placed in multiples of package quantity listed.

Product specifications

Used with

XTRE control relays

Number Of Poles

Two-pole

Type

Contactory Accessory - Auxiliary Contact

Frame size

D-G

Terminals

Screw

Contact configuration

1 NO-1 NC

Mounting method

Front

Conventional thermal current

16A

Quantity

5

Resources

Specifications and datasheets

[Eaton Specification Sheet - XTCEXFAG11](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)