

Eaton XTCEXSAB01

Catalog Number: XTCEXSAB01

Contactor Accessory - Auxiliary Contact, One-pole, Screw terminals, B Frame size, 1NC contact configuration, 16A conventional thermal rating, Side mounting, used with XTCEXSAB_



General specifications

Product Name	Catalog Number
Eaton motor control auxiliary contact	XTCEXSAB01
UPC	Product Length/Depth
786685244075	2 in
Product Height	Product Width
1.75 in	4 in
Product Weight	Warranty
0.1 lb	Not Applicable
Compliances	Certifications
CCC Marked	IEC 60947
CE Marked	EN 60947
ATEX Compliant	UL Listed
	CSA Certified

Catalog Notes

Frames B-C cannot use both a side AND a top mount auxiliary contact at the same time. Can only be mounted to the left side of contactor. Cannot be used in combination with front (top) mount auxiliary contacts or mechanical interlocks.

Product specifications

Used with

XTCEXSAB_

Type

Contactory Accessory - Auxiliary Contact

Frame size

B

Terminals

Screw

Contact configuration

1 NC

Mounting method

Side

Conventional thermal current

16A

Quantity

1

Resources

Specifications and datasheets

[Eaton Specification Sheet - XTCEXSAB01](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)

Eaton XTCEXSAB01

Catalog Number: XTCEXSAB01

Contactor Accessory - Auxiliary Contact, One-pole, Screw terminals, B Frame size, 1NC contact configuration, 16A conventional thermal rating, Side mounting, used with XTCEXSAB_



General specifications

Product Name	Catalog Number
Eaton motor control auxiliary contact	XTCEXSAB01
UPC	Product Length/Depth
786685244075	2 in
Product Height	Product Width
1.75 in	4 in
Product Weight	Warranty
0.1 lb	Not Applicable
Compliances	Certifications
CCC Marked	IEC 60947
CE Marked	EN 60947
ATEX Compliant	UL Listed
	CSA Certified

Catalog Notes

Frames B-C cannot use both a side AND a top mount auxiliary contact at the same time. Can only be mounted to the left side of contactor. Cannot be used in combination with front (top) mount auxiliary contacts or mechanical interlocks.

Product specifications

Used with

XTCEXSAB_

Type

Contactory Accessory - Auxiliary Contact

Frame size

B

Terminals

Screw

Contact configuration

1 NC

Mounting method

Side

Conventional thermal current

16A

Quantity

1

Resources

Specifications and datasheets

[Eaton Specification Sheet - XTCEXSAB01](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)