



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1121 W. 16th Street
75455-0000, TX Mt. Pleasant
Phone: 903-577-7311
Fax: 903-577-7320



YA28L2 4/0AWG 1/4"STD 1H Cu CMP Lug Burndy LLC

Catalog Number	YA28L2
Manufacturer	Burndy LLC
Description	4/0 Awg Cu, One Hole, 1/4 Stud Size, Standard Barrel, Inspection Window, Internal Chamfer, Tin Plated, UI/Csa 90 Up to 35KV, Purple Color Code, 15 Die Index.
Weight per unit	0.0900 (lbs/each)
Product Category	Large Terminals & Connectors

Features

Die Index	15
Material	Copper
pallet quantity	22200
Voltage Rating	35

Material, Color, and Finish

Color Code	PURPLE
------------	--------

Descriptions

Description	4/0AWG 1/4"STD 1H CU CMP LUG
extra long description	BUR YA28L2 4/0 CU 1-HOLE SHORT 1/4
Long Description	4/0 AWG CU, One Hole, 1/4 Stud Size, Standard Barrel, Inspection Window, Internal Chamfer, Tin Plated, UL/CSA 90 Up to 35kV, PURPLE Color Code, 15 Die Index.
Product Type	Terminal
Special Features	Features: UL Listed 90 DEG C, 600 V - 35 KV, 45 DEG And 90 DEG Angles Are Available, Temperature Rating: 90 DEG C, Wire Strip Length: 1-1/8 IN, Finish: Electro-Tin Plated, Tongue Angle: Straight, Die Index: 15, Tools, Die Set Catalog Number, And (number Of Crimps): Mechanical: MD6, OUR840, MD7-34R Tool, W28VT, W28RT Die, (2), X28RT Die, (3), Hydraulic: BCT500HS, Y500CTHS Tool, W28VT, W28RT Die, (2), X28RT Die, (3), Y35, Y39, Y750, PAT750 Tool, U28RT Die, (1), Y46 Tool, U28RT Die With PUADP-1 Adapter, (1),

Manufacturer Information

Brand	BURNDY
GTIN	00781810554111
Manufacturers Part Number	YA28L2
UPC	781810554111

Taxonomies, Classifications, and Categories

Type	Standard Barrel, Tin Plated
------	-----------------------------



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1121 W. 16th Street
75455-0000, TX Mt. Pleasant
Phone: 903-577-7311
Fax: 903-577-7320

Packaging

Carton	1
Package	100
Weight Per each	0.09

Uses, Certifications, and Standards

Application	Wire Termination
standard	UL 486A-486B