

ELLIOTT ELECTRIC SUPPLY 7604 Gateway Blvd 77521-0000, TX Baytown Phone: 832-514-7819 Fax: 832-514-7820



YGLR29C34 2-250 Ground Grid to 3/4 Ro Burndy LLC

Catalog Number	YGLR29C34
Manufacturer	Burndy LLC
Description	Copper Compression Connector, Ground Rod to Grid, 2 Awg (STR) to 250 Kcmil, 3/4" Ground Rod.
Weight per unit	0.9900 (lbs/each)
Product Category	Large Terminals & Connectors
atures	
Die Index	997
Material	Copper
pallet quantity	• •
scriptions	
Description	2-250 GROUND GRID TO 3/4 RO
extra long description	BUR YGLR29C34 2-250 GRD GRID TO 3/4
Long Description	Copper Compression Connector, Ground Rod to Grid, 2 AWG (Stito 250 kcmil, 3/4" Ground Rod.
Product Type	Compression
Special Features	Features: Ground Grid Connector For A Wide Range Of Copper Cable To Ground Rod, Provides High Torque Strength On Ground Rod, UL467 Listed, Acceptable For Direct Burial In Earth And Concrete, Prefilled With PENETROX Compound And Strip Sealed, Ground Rod Size: 3/4 IN, Conductor Size (run - Mm): 35 -120 SQ-MM, Conductor Type: Run: Copperweld, Commercial Stranded Copper, Metric Stranded Cable, Conductor Size (run - Range): Copperweld: 91.65 - 248.8 KCMIL, Code: 2 AWG - 250 KCMIL, Tools, Die Set Catalog Number,
anufacturer Information	
Brand	BURNDY
GTIN	00781810220825
Manufacturers Part Number	YGLR29C34
UPC	781810220825
konomies, Classifications, and	Categories
Category Description	SERVICE ENTRANCE FITTINGS: Weatherheads & Grounding Fittings & Ground Rods

Taxo

Category Description	SERVICE ENTRANCE FITTINGS: Weatherheads & Grounding
	Fittings & Ground Rods
Туре	Taps

Packaging

Carton 1	
Package 6	
Weight Per each 0.99	

7604 Gateway Blvd 77521-0000, TX Baytown Phone: 832-514-7819 Fax: 832-514-7820

Uses, Certifications, and Standards

Application	For Direct Burial In Earth And Concrete
standard	UL467;IEEE 837;IEEE 837 2014 Qualified